

EDITORIAL INDEX

Listed by subject are all articles that appeared in *MICROWAVE SYSTEMS NEWS*, Volume 18, January through December 1988. The key provides information on article type and/or magazine section. Single copies of *MSN* may be purchased for \$4 each. Reprints of *MSN* articles are available on a custom printing basis at reasonable prices in quantities of 500 or more. For more information, contact Cardiff Publishing Co., Inc., 6300 S. Syracuse Way, Suite 650, Englewood, CO 80111; Tel: (303) 220-0600; or 1170 East Meadow Drive, Palo Alto, CA 94303; Tel: (415) 494-2800.

(CF) - Cover Feature
(EU) - Euroform
(HR) - Human Resources
(PF) - Product Feature
(SF) - Special Feature
(TA) - Technical Article
(OP) - Opinion

AMPLIFIERS

Balanced Amplifier Designed to Provide 22.5 dB Gain (PF), November, p.54
Combined System Makes Fast Amplifier Compression and NF Measurements (TA), August, p.52
Designing an Ultrawideband Monolithic Distributed Amplifier (TA), July, p.28
Dual-Mode 20-GHz Downlink TWT for the ACTS Satellite (TA), May, p.50
Logarithmic Amplifiers Have 80 dB Typical Dynamic Range (PF), May, p.174
Low-Current MMIC Amplifier for Military EW Modules (CF), July, p.8
Output Noise of a High-Power Amplifier (TA), April, p.93
Radiation Effect on Microwave-Amplifier Performance (TA), March, p.56
Shrunken Helix Allows Expansion to K Band (26.5 GHz) for TWT Amplifiers (PF), September, p.114
Silicon MMIC Amplifier Challenges GaAs in Performance (PF), November, p.50
A Solid-State Microwave Pulsed-Power Amplifier (CF), May, p.8
Traveling-Wave-Tube Amplifier Design Considerations (TA), April, p.46
Versatile Amplifier Cuts Down on Tuning Time, Complex Hybrids (PF), October, p.98

ANTENNAS

Automatic Antenna-Alignment System (TA), June, p.58
Design Considerations for Tactical Field Radios (TA), October, p.43
Developing a Standard-C Antenna (TA), June, p.52
Electronically Steered Phased-Array Antenna for MSAT (TA), November, p.41
Enhancing the Accuracy of Direction-Finding EW Systems (TA), September, p.52
Fundamentals of Antenna Test and Evaluation (CF), June, p.8
Large Millimeter-Wave Antenna Systems (CF), December, p.19
Millimeter-Wave Tactical/Small-Aperture Antennas (TA), December, p.41
Multiple-Beam Antennas for Military Satellite Communications (CF), October, p.20
The Sinuous Antenna (TA), June, p.40

Spinning DF Antenna Systems in Modern Electronic Warfare (CF), September, p.22
System Integration Pitfalls (TA), January, p.104

COMMUNICATION

Design Considerations for Tactical Field Radios (TA), October, p.43
Digital Troposcatter Communications Systems (TA), October, p.69
Dual-Mode 20-GHz Downlink TWT for the ACTS Satellite (TA), May, p.50
Integrated E-Plane Mm-Wave 29-GHz Transceiver (EU), January, p.98B
Miniature Integrated X-Band Transceiver (TA), January, p.42
MMIC Modules for Active Phased-Array Applications in Communications Satellites (CF), November, p.20
Multiple-Beam Antennas for Military Satellite Communications (CF), October, p.20
New Test Set Helps Maintain Vital FAA Communications Links (CF), March, p.8
Stable Source Aids Automated Noise-Parameter Measurements (TA), February, p.51
Unattended Spectrum Monitoring of a Communications Satellite (TA), November, p.39

COMPONENTS & DEVICES

CW Source Provides Pulsed Microwave Signals (TA), January, p.59
Determining Bandwidth Ratios for Chebyshev Bandpass Filters (TA), July, p.72
Digitally-Controlled Biphase Modulators Operate to 18 GHz (PF), May, p.173
Double-Sideband Downconverter Operates at Center Frequency of 60 GHz (PF), October, p.96
Drop-in MM/W Downconverters Expand to W Band (PF), November, p.55
DTOs and Synthesizers Have Better Than -12 dBc Harmonic Output (PF), May, p.173
Dual-Axis Gimbal Attains 2000/Sec.2 Angular Acceleration (PF), June, p.110
High-Performance 20-GHz Package for GaAs MMICs (CF), January, p.10
J-Q Vector Modulator-The Ideal Control Component? (TA), May, p.105

MMIC SP3T, SP4T Switches Designed for 30-dB Isolation From DC to 6 GHz (PF), July, p.76
QPSK Modulators Produce RF Output to 270 Degrees (PF), May, p.174
Rugged, High-Performance 1 to 500 MHz Surface-Mount Mixer (PF), January, p.118
Simple Driving Techniques for GaAs MMIC Switches (TA), July, p.61
Stand-Alone Bias Tee Will Pass 1W Maximum RF Power (PF), May, p.175
Using Soft-Board MICs to Make Conventional Image-Reject Mixers (TA), May, p.73

COMPUTERS, MICROPROCESSORS & SOFTWARE

Adaptive Calibration Software for HP Network Analyzers (PF), June, p.111
Designing Active Filters (TA), March, p.64
Embedded RF Signal-Path Evaluation by Coherent FFT (TA), March, p.32
Noise-Reducing Effects of Signal Processing With an FFT (TA), March, p.44
S-Parameter Output From Spice Program (TA), February, p.63
Synthesizing Broadband Matching Networks of Arbitrary Structure (TA), January, p.98
Tips for Processing Microwave Circuit Boards (TA), February, p.78
Using Small Computers as Calibrated RF Diagnostic Tools (TA), May, p.156

COUNTERMEASURES

Large Millimeter-Wave Antenna Systems (CF), December, p.19
Millimeter-Wave Tactical/Small-Aperture Antennas (TA), December, p.41
Satellite-Jamming Design Considerations (Part 1), September, p.35

DESIGN

Applying TRL Calibration for Noncoaxial Measurements (TA), March, p.91
Automatic Processes and Controls for GaAs

EDITORIAL INDEX

Listed by subject are all articles that appeared in *MICROWAVE SYSTEMS NEWS*, Volume 18, January through December 1988. The key provides information on article type and/or magazine section. Single copies of *MSN* may be purchased for \$4 each. Reprints of *MSN* articles are available on a custom printing basis at reasonable prices in quantities of 500 or more. For more information, contact Cardiff Publishing Co., Inc., 6300 S. Syracuse Way, Suite 650, Englewood, CO 80111; Tel: (303) 220-0600; or 1170 East Meadow Drive, Palo Alto, CA 94303; Tel: (415) 494-2800.

(CF) - Cover Feature
(EU) - Euroform
(HR) - Human Resources
(PF) - Product Feature
(SF) - Special Feature
(TA) - Technical Article
(OP) - Opinion

AMPLIFIERS

Balanced Amplifier Designed to Provide 22.5 dB Gain (PF), November, p.54
Combined System Makes Fast Amplifier Compression and NF Measurements (TA), August, p.52
Designing an Ultrawideband Monolithic Distributed Amplifier (TA), July, p.28
Dual-Mode 20-GHz Downlink TWT for the ACTS Satellite (TA), May, p.50
Logarithmic Amplifiers Have 80 dB Typical Dynamic Range (PF), May, p.174
Low-Current MMIC Amplifier for Military EW Modules (CF), July, p.8
Output Noise of a High-Power Amplifier (TA), April, p.93
Radiation Effect on Microwave-Amplifier Performance (TA), March, p.56
Shrunken Helix Allows Expansion to K Band (26.5 GHz) for TWT Amplifiers (PF), September, p.114
Silicon MMIC Amplifier Challenges GaAs in Performance (PF), November, p.50
A Solid-State Microwave Pulsed-Power Amplifier (CF), May, p.8
Traveling-Wave-Tube Amplifier Design Considerations (TA), April, p.46
Versatile Amplifier Cuts Down on Tuning Time, Complex Hybrids (PF), October, p.98

ANTENNAS

Automatic Antenna-Alignment System (TA), June, p.58
Design Considerations for Tactical Field Radios (TA), October, p.43
Developing a Standard-C Antenna (TA), June, p.52
Electronically Steered Phased-Array Antenna for MSAT (TA), November, p.41
Enhancing the Accuracy of Direction-Finding EW Systems (TA), September, p.52
Fundamentals of Antenna Test and Evaluation (CF), June, p.8
Large Millimeter-Wave Antenna Systems (CF), December, p.19
Millimeter-Wave Tactical/Small-Aperture Antennas (TA), December, p.41
Multiple-Beam Antennas for Military Satellite Communications (CF), October, p.20
The Sinuous Antenna (TA), June, p.40

Spinning DF Antenna Systems in Modern Electronic Warfare (CF), September, p.22
System Integration Pitfalls (TA), January, p.104

COMMUNICATION

Design Considerations for Tactical Field Radios (TA), October, p.43
Digital Troposcatter Communications Systems (TA), October, p.69
Dual-Mode 20-GHz Downlink TWT for the ACTS Satellite (TA), May, p.50
Integrated E-Plane Mm-Wave 29-GHz Transceiver (EU), January, p.98B
Miniature Integrated X-Band Transceiver (TA), January, p.42
MMIC Modules for Active Phased-Array Applications in Communications Satellites (CF), November, p.20
Multiple-Beam Antennas for Military Satellite Communications (CF), October, p.20
New Test Set Helps Maintain Vital FAA Communications Links (CF), March, p.8
Stable Source Aids Automated Noise-Parameter Measurements (TA), February, p.51
Unattended Spectrum Monitoring of a Communications Satellite (TA), November, p.39

COMPONENTS & DEVICES

CW Source Provides Pulsed Microwave Signals (TA), January, p.59
Determining Bandwidth Ratios for Chebyshev Bandpass Filters (TA), July, p.72
Digitally-Controlled Biphase Modulators Operate to 18 GHz (PF), May, p.173
Double-Sideband Downconverter Operates at Center Frequency of 60 GHz (PF), October, p.96
Drop-in MM/W Downconverters Expand to W Band (PF), November, p.55
DTOs and Synthesizers Have Better Than -12 dBc Harmonic Output (PF), May, p.173
Dual-Axis Gimbal Attains 2000/Sec.2 Angular Acceleration (PF), June, p.110
High-Performance 20-GHz Package for GaAs MMICs (CF), January, p.10
J-Q Vector Modulator-The Ideal Control Component? (TA), May, p.105

MMIC SP3T, SP4T Switches Designed for 30-dB Isolation From DC to 6 GHz (PF), July, p.76
QPSK Modulators Produce RF Output to 270 Degrees (PF), May, p.174
Rugged, High-Performance 1 to 500 MHz Surface-Mount Mixer (PF), January, p.118
Simple Driving Techniques for GaAs MMIC Switches (TA), July, p.61
Stand-Alone Bias Tee Will Pass 1W Maximum RF Power (PF), May, p.175
Using Soft-Board MICs to Make Conventional Image-Reject Mixers (TA), May, p.73

COMPUTERS, MICROPROCESSORS & SOFTWARE

Adaptive Calibration Software for HP Network Analyzers (PF), June, p.111
Designing Active Filters (TA), March, p.64
Embedded RF Signal-Path Evaluation by Coherent FFT (TA), March, p.32
Noise-Reducing Effects of Signal Processing With an FFT (TA), March, p.44
S-Parameter Output From Spice Program (TA), February, p.63
Synthesizing Broadband Matching Networks of Arbitrary Structure (TA), January, p.98
Tips for Processing Microwave Circuit Boards (TA), February, p.78
Using Small Computers as Calibrated RF Diagnostic Tools (TA), May, p.156

COUNTERMEASURES

Large Millimeter-Wave Antenna Systems (CF), December, p.19
Millimeter-Wave Tactical/Small-Aperture Antennas (TA), December, p.41
Satellite-Jamming Design Considerations (Part 1), September, p.35

DESIGN

Applying TRL Calibration for Noncoaxial Measurements (TA), March, p.91
Automatic Processes and Controls for GaAs

EDITORIAL INDEX

MMIC Manufacturing (TA), July, p.40
Broadband, HF to VHF, Programmable Step Attenuator (TA), March, p.100
Buying a Digital Oscilloscope (TA), January, p.70
CW Source Provides Pulsed Microwave Signals (TA), January, p.59
Design Considerations for Tactical Field Radios (TA), October, p.43
Designing Active Filters (TA), March, p.64
Designing Low-Cost Cavity Combine Filters (TA), May, p.63
Designing Modern Electronic-Intelligence Systems (TA), September, p.68
Designing an Ultrawideband Monolithic Distributed Amplifier (TA), July, p.28
Determining Bandwidth Ratios for Chebyshev Bandpass Filters (TA), July, p.72
Developing a Standard-C Antenna (TA), June, p.52
Dual-Mode 20-GHz Downlink TWT for the ACTS Satellite (TA), May, p.50
Enhancing the Accuracy of Direction-Finding EW Systems (TA), September, p.52
Evaluating and Integrating Connectorless (Drop-In) Microwave Components (TA), April, p.65
High-Performance 20-GHz Package for GaAs MMICs (CF), January, p.10
Interaction Between Component and System Design Examined for Radar Development (TA), April, p.28
Master Clocks for Improving Overall System Performance (TA), August, p.62
MIL-Specification Mixers Simplify Military Systems Design (TA), July, p.56
Miniature Integrated X-Band Transceiver (TA), January, p.42
MMIC SP3T, SP4T Switches Designed for 30-dB Isolation From DC to 6 GHz (PF), July, p.76
MMW Radio-Astronomical Imaging Instrumentation (TA), December, p.74
A Modified PTFE Microwave Circuit Substrate (TA), February, p.36
Next-Generation High-Speed Packaging (TA), January, p.32
Output Noise of a High-Power Amplifier (TA), April, p.93
Radiation Effect on Microwave Amplifier Performance (TA), March, p.56
Redundancy Solves Ambiguity in ATE System Test (Part I) (TA), March, p.80
Redundancy Solves Ambiguity in ATE System Test (Part II) (TA), April, p.107
Satellite-Jamming Design Considerations (Part I) (TA), September, p.35
Satellite-Jamming Design Considerations (Part II) (TA), October, p.32
A Solid-State Microwave Pulsed-Power Amplifier (CF), May, p.8
Spinning DF Antenna Systems in Modern Electronic Warfare (CF), September, p.22
S-Parameter Output From Spice Program (TA), February, p.63
Statistical Calibration Assures Accurate Vector (TA), March, p.70
Substrates for Hybrid Microelectronic Applications (TA), February, p.21
Synthesizing Broadband Matching Networks of Arbitrary Structure (TA), January, p.98
System Integration Pitfalls (TA), January, p.104
Tips for Processing Microwave Circuit Boards (TA), February, p.78
Traveling-Wave-Tube Amplifier Design Considerations (TA), April, p.46
Trimming of Monolithic-Microwave Integrated Circuits (TA), February, p.46
Verification of RF Designs Using Low-Cost Software (TA), April, p.97
Using Soft-Board MICs to Make Conventional Image-Reject Mixers (TA), May, p.73
Wideband Digitally Tuned Oscillator Technology for Electronic Defense (TA), July, p.46

INDUSTRY NEWS & DEVELOPMENTS

Broadband Threshold Detectors Optimized for Built-In Test (PF), April, p.123
Embedded RF Signal-Path Evaluation by Coherent FFT (TA), March, p.32
Integrated E-Plane Mm-Wave 29 GHz Transceiver (EU), January, p.98B
Microwave Network Analyzer Is Completely Integrated (PF), April, p.125
Military Microwaves 88 Conference and Exhibition (SF), April, p.115
Microwave Component Distribution Comes of Age (SF), May, p.144
Microwave Test Equipment I/M Where Next? (OP), August, p.30
1988 GaAs IC Show Heads to Nashville (SF), October, p.83
Profile of the RF and Microwave Industries (SF), May, p.155
Smart Munitions I/M Are They Affordable (OP), December, p.32
Solution-Oriented Economics, the Growth Path for GaAs ICs, (O), October, p.77
Test Systems Architecture for the Future (TA), August, p.42
Who Says Noise is a Niche Market? (OP), August, p.70

MATERIALS

Fabricating PTFE/Glass Microwave Circuits (CF), February, p.8
High-Performance 20 GHz Package for GaAs MMICs (CF), January, p.10
A Modified PTFE Microwave Circuit Substrate (TA), February, p.36
Next-Generation High-Speed Packaging (TA), January, p.32
Packaging High-Speed Multigigahertz GaAs Digital Integrated Circuits (Part I) (TA), January, p.94
Packaging High-Speed Multigigahertz GaAs Digital Integrated Circuits (Part II) (TA), February, p.68
Qualification Problems Affect PTFE Microwave-Circuit-Board Development (TA), February, p.86
Substrate for Hybrid Microelectronic Applications (TA), February, p.2
Tips for Processing Microwave Circuit Boards (TA), February, p.78
Using Thin Films and Metallo-Organic Deposition for Advanced Packaging (TA), January, p.80

MEASUREMENT

Applying TRL Calibration for Noncoaxial Measurements (TA), March, p.91
Automatic Antenna-Alignment System (TA), June, p.58
Bandwidth Effects in Noise-Filter Measurements (TA), April, p.77
Buying a Digital Oscilloscope (TA), January, p.70
A Closer Look at Noninsertable-Device Measurements (TA), June, p.65
Combined System Makes Fast Amplifier Compression and NF Measurements (TA), August, p.52
High-Performance 20-GHz Package for GaAs MMICs (CF), January, p.10
Low-level Power-Measurement Techniques and Accuracy (TA), June, p.86
Microwave Network Analyzer Is Completely Integrated (PF), April, p.125

Modeling Phase-Noise Measurement Systems (TA), June, p.96
New Digital Spectrum Analyzer Solves Difficult Measurement Problems (CF), August, p.8
New Test Set Helps Maintain Vital FAA Communications Links (CF), March, p.8
Noise of Cascaded Two-Part Devices of Unequal Bandwidths (TA), May, p.129
Packaging High-Speed Multigigahertz GaAs Digital Integrated Circuits (Part I) (TA), January, p.94
Packaging High-Speed Multigigahertz GaAs Digital Integrated Circuits (Part II) (TA), February, p.68
Radar Cross-Section and Imaging Measurement Systems (CF), April, p.8
Stable Source Aids Automated Noise-Parameter Measurements (TA), February, p.51
Using Small Computers as Calibrated RF Diagnostic Tools (TA), May, p.156

MILLIMETER-WAVE TECHNOLOGY

Broadband Millimeter-Wave IC Doubler Has 20-dB Isolation Between Input and Output Ports (PF), August, p.78
Drop-In MM/W Downconverters Expand to W Band (PF), November, p.55
Double-Sideband Downconverter Operates at Center Frequency of 60 GHz (PF), October, p.96
Integrated E-Plane Mm-Wave 29-GHz Transceiver (TA), September, p.99
Large Millimeter-Wave Antenna Systems (CF), December, p.19
Low-Current MMIC Amplifier for Military EW Modules (CF), July, p.8
Millimeter-Wave Tactical/Small-Aperture Antennas (TA), December, p.41
Millimeter-Wave Radar Seekers: An Historical Perspective (TA), December, p.63
MMIC Attenuator Chip Has Input/Output Match to 50 GHz (PF), November, p.56
MMW Radio-Astronomical Imaging Instrumentation (TA), December, p.74
Radar Transceiver for Smart-Munitions Applications (TA), September, p.92

MONOLITHIC MICROWAVES

Automatic Processes and Controls for GaAs MMIC Manufacturing (TA), July, p.40
Designing an Ultrawideband Monolithic Distributed Amplifier (TA), July, p.28
High-Performance 20 GHz Package for GaAs MMICs (CF), January, p.10
Low-Current MMIC Amplifier for Military EW Modules (CF), July, p.8
MMIC Modules for Active Phased-Array Applications in Communications Satellites (CF), November, p.20
Next-Generation High-Speed Packaging (TA), January, p.32
Silicon MMIC Amplifier Challenges GaAs In Performance (PF)
Trimming of Monolithic-Microwave Integrated Circuits (TA), February, p.46

RADAR

Advanced Millimeter-Wave Solid-State-Device Research (TA), December, p.68
Interaction Between Component and System Design Examined for Radar Development (TA), April, p.28
Millimeter-Wave Radar Seekers: An Historical

IN
XIX

OL

8

88

MI

EDITORIAL INDEX

Perspective (TA), December, p.63
 New Digital Spectrum Analyzer Solves Difficult Measurement Problems (CF), August, p.8
 Noise-Reducing Effects of Signal Processing With an FFT (TA), March, p.44
 Radar Cross-Section and Imaging Measurement Systems (CF), April, p.8
 Radar Transceiver for Smart-Munitions Applications (TA), September, p.92
 System Integration Pitfalls, (TA), January, p.104
 Time and Frequency Standards From GPS (TA), June, p.72
 Understanding Radar-Cross-Section Measurements (TA), October, p.54
 Weather Radar in General Aviation (TA), April, p.38

SATELLITES

Dual-Mode 20-GHz Downlink TWT for the ACTS Satellite (TA), May, p.50
 Electronically-Steered Phased-Array Antenna for MSAT (TA), November, p.41
 MMIC Modules for Active Phased-Array Applications in Communications Satellites (CF), November, p.20
 Multiple-Beam Antennas for Military-Satellite Communications (CF), October, p.20
 RF Development for Mobile-Satellite Systems (TA), November, p.2
 Satellite-Jamming Design Considerations (Part I) (TA), September, p.35
 Satellite-Jamming Design Considerations (Part II) (TA), October, p.32
 Unattended Spectrum Monitoring of a Communications Satellite (TA), November, p.39

SEMINARS & CONFERENCES

AFCEA Celebrates 42nd International Convention and Exposition (SF), June, p.34
 GaAs IC Show Heads to Nashville (TA), October, p.83
 Highlights of the ARFTG Meeting in New York (SF), August, p.28
 International Telemetry Conference Returns to Las Vegas (TA), September, p.110
 Military Microwaves '88 Conference & Exhibition (SF), April, p.115
 1988 IEEE MTT/S International Microwave Symposium, May 24 to 27 (SF), May, p.30

SIGNAL PROCESSING

Designing Modern Electronic-Intelligence Systems (TA), September, p.68
 Embedded RF Signal-Path Evaluation by Coherent FFT (TA), March, p.32
 Enhancing the Accuracy of Direction-Finding EW Systems (TA), September, p.52
 I-Q Vector Modulator-The Ideal Control Component? (TA), May, p.105
 Noise Reducing Effects of Signal Processing With an FFT (TA), March, p.44
 Synthesizer Switches at 1 ms. (PF), August, p.74

SOLID-STATE

Advanced Millimeter-Wave Solid-State-Device Research (TA), December, p.68
 A Solid-State Microwave Pulsed-Power Amplifier (CF), May, p.8
 Wideband Digitally Tuned Oscillator Technology for Electronic Defense (TA), July, p.46

TEST & MEASUREMENT

Bandwidth Effects in Noise-Figure Measurements (TA), April, p.77
 Broadband HF to VHF, Programmable Step Attenuator (TA), March, p.100
 Broadband Threshold Detectors Optimized for Built-in Test (PF), April, p.123
 Buying a Digital Oscilloscope (TA), January, p.70
 Combined System Makes Fast Amplifier Compression and NF Measurements (TA), August, p.52
 CW Source Provides Pulsed Microwave Signals (TA), January, p.59
 Designing Active Filters (TA), March, p.64
 Dynamic Range Extender Operates Over 100 dB at 2 to 20 GHz (PF), July, p.78
 Embedded RF Signal-Path Evaluation by Coherent FFT (TA), March, p.32
 Evaluating and Integrating Connectorless (Drop-In) Microwave Components (TA), April, p.165
 Fundamentals of Antenna Test and Evaluation (CF), June, p.8
 Low-Cost Sweep Generators (PF), June, p.107
 Low-Level Power-Measurement Techniques and Accuracy (TA), June, p.86
 Microwave Network Analyzer Is Completely Integrated (PF), April, p.125
 Microwave Synthesizer Series 1700 Expands to Reach 26.5 GHz (PF), October, p.99
 Microwave Test Equipment I/M Where Next? (LO), August, p.30
 Network Analyzer Characterizes Pulsed-RF Devices (PF), August, p.76
 New Digital Spectrum Analyzer Solves Difficult Measurement Problems (CF), August, p.8
 New Test Set Helps Maintain Vital FAA Communications Links (CF), March, p.8
 Noise Parameter Test Set Operates From 6 to 18 GHz (PF), May, p.172
 "Portable" Means More Than "Easy to Carry" (TA), May, p.116
 Qualification Problems Affect PTFE Microwave-Circuit-Board Development (TA), February, p.86
 Redundancy Solves Ambiguity in ATE System Test (Part I) (TA), March, p.80
 Redundancy Solves Ambiguity in ATE System Test (Part II) (TA), April, p.107
 Shrunk Helix Allows Expansion to KBand (26.5 GHz) for TWT Amplifiers (PF), September, p.114
 Stable Source Aids Automated Noise-Parameter Measurements (TA), February, p.51
 Statistical Calibration Assures Accurate Vector (TA), March, p.70
 Test Systems Architecture for the Future (TA), August, p.42
 Unattended Spectrum Monitoring of a Communications Satellite (TA), November, p.39
 Understanding Radar-Cross-Section Measurements (TA), October, p.54
 Using Small Computers as Calibrated RF Diagnostic Tools (TA), May, p.156
 Vector Voltmeter Covers 100KHz to 2GHz (PF), May, p.175
 VME-Based Processing Chassis Added to System 500 (PF), September, p.119

TUBES

Miniature Magnetrons for Coherent High-Duty Operation (TA), May, p.166
 Shrunk Helix Allows Expansion to K Band (26.5 GHz) for TWT Amplifiers (TA), September, p.114

WRITING FOR MSN IS A REWARDING EXPERIENCE

★★★ Reward #1 ★★★

The satisfaction of contributing to your profession

★★★ Reward #2 ★★★

Recognition by your peers

★★★ Reward #3 ★★★

We pay an honorarium to our authors

For 1989, MSN needs articles on the following topics, plus other timely subjects of importance to the microwave system designer:

Radar Technology
 Monolithic Circuits
 Microwave ATE
 C/I Topics
 Commercial Applications
 High Power Systems

... and much more.

For more information and an Author's Guide, contact Les Besser at:

MSN
 1170 E. Meadow Drive
 Palo Alto, CA 94303

